



Product

BK and BF Series Geared Motors

Application

Asphalt Mixing Plant

Highlights

- BK and BF Series geared motors feature a hardened wear sleeve and spray ring
- Complies with NA and International standards, including NEMA, IEC, CSA, and CE
- Torque rating to 18500 Nm
- Low noise gearing
- IP65 Enclosure (Standard), IP66 (Optional)
- Completely enclosed, sealed against dust and moisture
- Corrosion protection CORO1, CORO2, CORO3
- Connection Standard with CAGE CLAMP[®]

A major international asphalt mixing plant OEM required rugged-duty geared motors for use on various applications within their plants. Belt conveyors, mounted under multiple sorting bins, feed various sized aggregate into a large dryer. Additional geared motors drive tiered flights of conveyors inside the dryer drum. A drive is also utilized on a screw conveyor which transfers the hot, dried aggregate to the base of an elevator. Geared motors are used to power the bucket elevator which delivers the aggregate up to a raised batching unit for weighing, separating, and mixing with mineral fillers.

Bauer application engineers provided technical advice during many visits with different customer engineering teams. Ultimately, Bauer gear motors were selected over competitive units due to Bauer's reputation for high-quality, well-engineered products, responsive delivery times and extensive global sales and service support.

To meet the customer's various application torque and speed change requirements, as well as space limitations, Bauer BK Series gear motors, size 40 to 90 were supplied for use on the various asphalt conveyors and elevator. Each dryer requires four BF Series gear motors.

Europe
+49 711 3518-0
bauergears.com

US
1-732-469-8770

Asia Pacific
For a list of our AP sales offices:
altramotion.com/contactus